

**ioLogik**  
**E1200 Series**

Remote I/O



Model Name	E1210	E1211	E1212	E1214	E1213**	E1240	E1241	E1242	E1260	E1262
Digital Inputs	16	-	8	6	8	-	-	4	-	-
Digital Outputs	-	16	-	-	4	-	-	-	-	-
Relays	-	-	-	6	-	-	-	-	-	-
Configurable DIOs	-	-	8	-	4	-	-	4	-	-
Analog Inputs	-	-	-	-	-	8	-	4	-	-
Analog Outputs	-	-	-	-	-	-	4	-	-	-
RTDs	-	-	-	-	-	-	-	-	6	-
Thermocouples	-	-	-	-	-	-	-	-	-	8
Ports (Connector)	2 (RJ45)									
Speed	10/100 Mbps									
Switch (Daisy Chain)	Yes									
Protocols	EtherNet/IP (Adapter), Modbus/TCP (slave), TCP/IP, UDP, DHCP, BOOTP, HTTP, SNMP v1/v2c, RESTful API									
Standard Models	-10 to 60°C (14 to 140°F)									
Wide Temp. Models	-40 to 75°C (-40 to 167°F)									
Hazardous Locations	Class 1 Division 2; ATEX Zone 2									
Warranty	5 years	5 years	5 years	2 years*	5 years	5 years	5 years	5 years	5 years	5 years

\*Because of the limited lifetime of power relays, products using that component are covered by a 2-year warranty.

\*\*DO of ioLogik E1213 is source type